# TOUGH TANKS FOR TOUGH JOBS

Tough • Affordable • Reliable



Double Wall
Cylindrical



Double Wall Rectangular



Single Wall Vertical



Above ground steel tanks manufactured for your application









## Introduction

From construction companies, farms, and ranches to vehicle service centers, our products are the solution for a tough, affordable and reliable storage and handling of hazardous and non-hazardous, flammable and combustible fluids including Biodiesel and Ethanol.

Across the country, our products are in use in the private and public sectors where containment of flammable and combustible fluids or other liquids are required. We provide liquid storage solutions for your application while assuring environmental safety and compliance with customer provided code requirements.

Eagle Tanks, Inc. products are fabricated in accordance with Underwriter Laboratories UL 142 standard. All of our tanks are shopfabricated under strict quality controls in accordance with the UL standard. Each unit is pressure tested at the factory to insure proper performance in the field.

We offer turnkey systems that arrive at your location and are ready to go. All that is left for you to do is the surface preparation and provide electricity to your system. We also offer the tank only without equipment for those who want to provide their own or do not require it for your application. We also manufacture tanks for chemical and water storage applications. Two product tanks are also available.

#### **Double Wall Horizontal** 240 to 20,000 Gallon Capacity

Double wall tanks are used in applications where 110% secondary containment is required. A double-wall cylindrical horizontal tank is a tank built within another tank. The primary tank is completely enclosed and protected. They are listed with Underwriter Laboratories, Inc. (UL) and are built to UL-142 standard.


This product line is available with skids with fork pockets and chain eyes. A tank with skids does not require extensive site preparation. With the tank empty, skids allow the tank to be easily transported by fork-lift, or dragged to a new location.

Skid Option: Heavy Duty Wide Flange I-Beam			
Length (gal)		Description (feet)	
5'-8'	286	Standard Duty Set	
9'-12'	375	Standard Duty Set	
13'-16'	450	Standard Duty Set	
17'-25'	665	Standard Duty Set	
21'-28'	2492	Heavy Duty Tri-skid	
30'-36'	2892	Heavy Duty Tri-skid	
Custom Skids - Call With Dimensions and We'll Quote			

Capacity		lorizontal Cylindrica  Dimensions	Gauge	Gauge
(gal)	(lbs)	(feet)	Primary	Seconda
	· · ·	,		
240	818	3'5"W x 3'10"H x 5'11"L		12
300	923	3'5"W x 3'10"H x 6'1"L	12	12
420	1113	4'W x 4'6"H x 6'L	12	12
520	1237	4'W x 4'6"H x 6'L	10	12
675	1486	4'W x 4'6"H x 9'L	10	12
750	1610	4'W x 4'6"H x 10'L	10	12
1000	1984	4'W x 4'6"H x 13'L	10	12
1100	2403	5'6"W x 5'8"H x 9'L	10	12
1200	2230	5'6"W x 5'8"H x 8'L	10	12
1500	2922	5'6"W x 5'8"H x 12'L	10	12
2000	4070	6'4"W x 6'6"H x 10'L	3/16	10
2500	4889	6'4"W x 6'6"H x 13'L	3/16	10
3000	5435	6'4"W x 6'6"H x 15'L	3/16	10
4000	7292	6'4"W x 6'6"H x 19'L	3/16	10
5000	10125	7'10"W x 8'4"H x 16'L	1/4	3/16
6000	11486	7'10"W x 8'4"H x 19'L	1/4	3/16
8000	13754	7'10"W x 8'4"H x 24'L	1/4	3/16
10000	15818	9'6"W x 9'9"H x 21'L	1/4	3/16
12000	18006	9'6"W x 9'9"H x 25'L	1/4	3/16
15000	20742	9'6"W x 9'9"H x 30'L	1/4	3/16
18000	24571	9'6"W x 9'9"H x 37'L	1/4	3/16
20000	25315	10'W x 10'3"H x 36'L	1/4	3/16
Double	Wall S	Split Horizontal Cylin	drical T	anks
420	1251	4'W x 4'6"H x 6'L	10	12
520	1375	4'W x 4'6"H x 7'L	10	12
675	1624	4'W x 4'6"H x 9'L	10	12
750	1748	4'W x 4'6"H x 10'L	10	12
1000	2122	4'W x 4'6"H x 13'L	10	12
1500	4025	5'6"W x 5'8"H x 12'L	10	12
	4584	6'4"W x 6'6"H x 10'L	3/16	10
2000		6'4"W x 6'6"H x 13'L	3/16	10
	5403			
2500	5403 5949		3/16	10
2500 3000	5949	6'4"W x 6'6"H x 15'L	3/16 3/16	10 10
2500 3000 4000	5949 7041	6'4"W x 6'6"H x 15'L 6'4"W x 6'6"H x 19'L	3/16	10
2000 2500 3000 4000 5000	5949 7041 10811	6'4"W x 6'6"H x 15'L 6'4"W x 6'6"H x 19'L 7'10"W x 6'4"H x 16'L	3/16 1/4	10 3/16
2500 3000 4000 5000 6000	5949 7041 10811 12172	6'4"W x 6'6"H x 15'L 6'4"W x 6'6"H x 19'L 7'10"W x 6'4"H x 16'L 7'10"W x 6'4"H x 19'L	3/16 1/4 1/4	10 3/16 3/16
2500 3000 4000 5000 6000 8000	5949 7041 10811 12172 14440	6'4"W x 6'6"H x 15'L 6'4"W x 6'6"H x 19'L 7'10"W x 6'4"H x 16'L 7'10"W x 6'4"H x 19'L 7'10"W x 8'4"H x 24'L	3/16 1/4 1/4 1/4	10 3/16 3/16 3/16
2500 3000 4000 5000 6000 8000	5949 7041 10811 12172 14440 17342	6'4"W x 6'6"H x 15'L 6'4"W x 6'6"H x 19'L 7'10"W x 6'4"H x 16'L 7'10"W x 6'4"H x 19'L 7'10"W x 8'4"H x 24'L 9'6"W x 9'9"H x 21'L	3/16 1/4 1/4 1/4 1/4	10 3/16 3/16 3/16 3/16
2500 3000 4000 5000 6000 8000	5949 7041 10811 12172 14440	6'4"W x 6'6"H x 15'L 6'4"W x 6'6"H x 19'L 7'10"W x 6'4"H x 16'L 7'10"W x 6'4"H x 19'L 7'10"W x 8'4"H x 24'L	3/16 1/4 1/4 1/4	10 3/16 3/16 3/16

Custom Tank - Call With Dimensions and We'll Quote







## Vertical Single Wall 1,000 to 35,000 Gallon Capacity

These tanks are used in applications where secondary containment is not required or already exists. These tanks are the most economical, with the highest gallon-for-the-dollar value.

Vertical Single Wall Cylindrical Tanks				
Capacity (gal)	Weight (lbs)	Dimensions (feet)	Gauge Primary	
240	260	3'2"D x 4'H	12	
300	306	3'2"D x 5'H	12	
340	326	3'10"D x 4'H	12	
420	380	3'10"D x 5'H	12	
520	434	3'10"D x 6'H	12	
675	543	3'10"D x 8'H	12	
750	768	3'10"D x 9'H	10	
1000	851	5'4"D x 6'H	10	
1500	1142	5'4"D x 9'H	10	
2000	2059	6'4"D x 9'6"H	3/16	
4000	3397	6'4"D x 18'H	3/16	
6000	4141	8'D x 17'H	3/16	
8000	4945	9'6"D x 16'H	3/16	
10000	5883	9'6"D x 20'H	3/16	
10000	5667	11'6"D x 14'H	3/16	
12000	6822	9'6"D x 24'H	3/16	
14000	7080	11'6"D x 9'H	3/16	
15000	7727	10'11"D x 23'H	3/16	
20000	9341	11'6"D x 27'H	3/16	
25000	10989	12'D x 31'H	3/16	
Custom Tank - Call With Dimensions and We'll Quote				

## Single Wall Horizontal 240 to 20,000 gallon capacity

Single Wall tanks are used in applications where secondary containment is not required or already exists. These tanks are an economical solution, with a high gallon-for-the-dollar value.

Capacity (gal)	Weight (lbs)	Dimensions (feet)	Gauge Primary
240	334	3'2"W x 4'H x 4'L	10
300	393	3'2"W x 4'H x 5'L	10
340	418	3'10"W x 4'H x 4'L	10
420	488	3'10"W x 4'H x 5'L	10
520	558	3'10"W x 4'H x 6'L	10
520	434	3'10"W x 4'H x 6'L	12
675	698	3'10"W x 4'H x 8'L	10
675	543	3'10"W x 4'H x 8'L	12
750	768	3'10"W x 4'H x 9'L	10
1000	851	5'4"W x 5'4"H x 6'L	10
1000	662	5'4"W x 5'4"H x 6'L	12
1000	978	3'10"W x 3'10"H x 12'L	10
1000	761	3'10"W x 3'10"H x 12'L	12
1500	1617	4'8"W x 4'8"H x 11'L	
2000	2353	6'4"W x 6'4"H x 9'L	3/16
2500	2667	6'4"W x 6'4"H x 11'L	3/16
3000	2982	6'4"W x 6'4"H x 13'L	3/16
3500	3297	6'4"W x 6'4"H x 15'L	3/16
4000	3611	6'4"W x 6'4"H x 17'L	3/16
5000	5107	7'10"W x 7'10"H x 14'L	3/16
6000	6583	7'8"W x 7'8"H x 18'L	3/16
10000	8823	9'6"W x 9'6"H x 19'L	3/16
12000	10375	9'6"W x 9'6"H x 23'L	3/16
15000	12251	9'6"W x 9'6"H x 29'L	3/16
20000	14519	10'W x 10'H x 34'L	3/16



888-678-0698 Toll-Free 503-448-1917 Local









## Rectangular Double Wall 120 to 1,000 gallon capacity

Rectangular Double Wall tanks are used in applications where space is limited, 110% secondary containment is required and capacity requirements is less than 1000 gallons. A double-wall rectangular tank is a tank built within another tank. If a double wall tank is not required, we offer single wall rectangular tanks as well.

The primary tank is completely enclosed and protected. They are built to UL-142 specifications.

## **Equipment**

There are many equipment solutions available for your application. Our standard equipment packages include all venting, nozzles, plumbing, adapters, valves and pumps that represent the industry standard in handling of flammable and combustible liquids. If you specify what you need, we'll help you get the equipment or refer you to an equipment distributor that can meet your needs.

#### **Accessories**

We offer a wide variety of accessories for your tank to meet your specific application:

- Pump mounts
- Manways
- Welded and Flanged Piping
- Equipment Platforms
- OSHA Ladders and Platforms
- Tank Stands
- Equipment Weather Cover
- Epoxy Coatings
- I-Beam Skids

## Don't see what you need for your application?

We can build from <u>your</u> specifications and drawings, or provide the drawings for your approval.

Call 1.888.678.0698 for a quote

Double Wall Rectangular Tanks				
Capacity (gal)	Weight (lbs)	Dimensions (feet)	Gauge Primary	
120	385	2'6"W x 4'H x 2'6"L	12	
150	491	3'W x 4'H x 2'2"L	12	
180	532	3'W x 4'H x 2'6"L	12	
200	614	3'W x 4'H x 3'2"L	12	
250	645	3'W x 4'H x 3'5"L	12	
280	696	3'W x 4'H x 3'10"L	12	
300	716	3'W x 4'H x 4'L	12	
350	778	3'W x 4'H x 4'6"L	12	
400	928	3'W x 4'H x 5'8"L	12	
500	969	3'W x 4'H x 6'L	12	
650	1299	3'W x 4'H x 8'L	10	
750	1112	3'W x 4'H x 9'L	10	
1000	1896	4'W x 4'H x 9'7"L	10	
Custom T	ank - Ca	all For Dimensions and Qu	ıote	

Single '	Single Wall Rectangular Tanks				
Capacity	Weight	Dimensions	Gauge	e	
(gal)	(lbs)	(feet)	Prima	ry	
100	192	3'W x 4'H x 1'2"L	12		
120	207	3'W x 4'H x 1'5"L	12		
150	228	3'W x 4'H x 1'9"L	12		
200	257	3'W x 4'H x 2'3"L	12		
250	294	3'W x 4'H x 2'10"L	12		
280	315	3'W x 4'H x 3'2"L	12		
300	330	3'W x 4'H x 3'5"L	12		
350	360	3'W x 4'H x 3'11"L	12		
400	396	3'W x 4'H x 4'6"L	12		
500	597	3'W x 4'H x 5'7"L	12		
650	729	3'W x 4'H x 7'3"L	10		
1000	1044	4'W x 4'H x 11'2"L	10		
Custom T	Custom Tank - Call For Dimensions and Quote				



Eagle Tanks, Inc. 9055 Porter Way SE Aumsville, OR 97325 info@eagletanks.com 888-678-0698 Toll-Free 503-448-1917 local 503-448-1927 fax

